

D-2912

2

This listing of claims will replace all prior versions, and listing, of claims in the application:

IN THE CLAIMS:

1. (previously presented) A container for releasing a chemical additive in a liquid fuel composition comprising:

a casing defining a fuel-impermeable wall structure, a substantially hollow interior and at least one opening in the wall structure;

a fuel additive composition provided in the interior of said casing, said fuel additive composition comprising a chemical additive soluble in a liquid fuel composition; and

at least one fuel-permeable element provided at or substantially directly adjacent the at least one opening of the casing and structured to be effective to provide for release of a portion of the chemical additive into the liquid fuel composition when the liquid fuel composition is in contact with the casing, the element comprising at least two different types of components, the types of components being selected from the group consisting of (1) a porous member, (2) a semi-permeable member, and (3) an at least partially fuel-soluble seal, provided that each of the components initially extends substantially across the at least one opening.

2. (previously presented) The container of claim 1 wherein the casing comprises a material selected from the group consisting of metals, polymeric materials, combinations thereof and mixtures thereof.

3. (original) The container of claim 2 wherein the material is selected from the group consisting of metals, polyvinyl chloride, polyethylene, polypropylene, nylon, polyethylene vinyl acetate, polypropylene vinyl acetate, combinations thereof and mixtures thereof.

D-2912

3

4. (original) The container of claim 1 wherein the casing is a substantially cylindrical-shaped casing.

5. (original) The container of claim 4 wherein the at least one opening comprises at least one open end of the cylindrical-shaped casing or at least one side opening in a sidewall of the cylindrical-shaped casing.

6. (original) The container of claim 1 wherein the casing is a substantially bowl-shaped casing.

7. (original) The container of claim 6 further comprising a cap member disposed across a top of the substantially bowl-shaped casing.

8. (original) The container of claim 6 wherein the at least one opening is located in a top of the substantially bowl-shaped casing, in a side of the substantially bowl-shaped casing or in a bottom of the substantially bowl-shaped casing.

9. (previously presented) The container of claim 1 wherein the at least one fuel-permeable element comprises the at least partially fuel soluble seal.

10. (previously presented) The container of claim 9 wherein the at least partially fuel-soluble seal comprises a support structure structured to support the at least partially fuel soluble seal, the support structure being coated with a fuel soluble polymer.

11. (original) The container of claim 10 wherein the support

D-2912

4

structure comprises a wire screen, a woven cloth or combinations thereof.

12. (previously presented) The container of claim 1 wherein the at least one fuel-permeable element includes the semi-permeable member.

13. (previously presented) The container of claim 1 wherein the at least one fuel-permeable element includes the porous member.

14. (previously presented) The container of claim 13 wherein the at least one fuel-permeable element further includes an at least one retention member effective in retaining the porous member in a substantially fixed position relative to the casing.

15. (previously presented) The container of claim 13 wherein the porous member is a microporous membrane having a pore size of between about 0.2 microns to about 100 microns.

16. (previously presented) The container of claim 13 wherein the porous member comprises a material selected from the group consisting of metals, glasses, polymeric materials, combinations thereof and mixtures thereof.

17. (canceled)

18. (previously presented) The container of claim 12 wherein the semi-permeable membrane comprises a material selected from the group consisting of metals, glasses, polymeric materials, papers, combinations thereof and mixtures thereof.

19. (original) The container of claim 1 wherein the at least

D-2912

5

one opening comprises a plurality of openings and the at least one fuel-permeable element comprises a corresponding plurality of fuel-permeable elements.

20. (original) The container of claim 1 wherein the fuel additive composition is provided in a particulate form.

21. (original) The container of claim 1 wherein the fuel additive composition is present in the casing in a liquid form.

22. (original) The container of claim 1 wherein the chemical additive is selected from the group consisting of dispersants/detergents, antioxidants, anti-wear agents, corrosion inhibitors, demulsifiers, flow improvers, lubricating agents, microbiocides and mixtures thereof.

23. (original) The container of claim 1 wherein the at least one fuel-permeable element is at least partially coated with a coating polymeric material.

Claims 24-25 (canceled)

26. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 1 in contact with the fuel composition.

27. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 4 in contact with the fuel composition.

28. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the

D-2912

6

container of claim 6 in contact with the fuel composition.

29. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 9 in contact with the fuel composition.

30. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 13 in contact with the fuel composition.

31. (previously presented) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 12 in contact with the fuel composition.

32. (previously presented) A seal assembly comprising:
a fuel-permeable membrane sized and structured to be positioned in or substantially directly adjacent an opening in a casing defining a hollow interior containing a fuel additive soluble in a fuel composition, the membrane is structured to be positioned so that substantially all of the additive leaving the hollow interior through the opening passes through the membrane, and

an at least partially fuel-soluble seal member sized and structured to be positioned relative to the opening in the casing to prevent additive leaving the hollow interior through the opening when the seal member is intact.

33. (currently amended) The seal ~~member~~ assembly of claim 32 wherein the seal member is structured to be compromised in the presence of the fuel composition, thereby allowing additive to leave the hollow interior through the opening.

D-2912

7

34. (canceled)

35. (original) The seal assembly of claim 32 wherein the seal member comprises a support structure and a fuel-soluble polymer.

36. (original) The seal assembly of claim 35 wherein the support structure includes at least one of a wire screen and a woven cloth.

37. (original) The seal assembly of claim 32 which further comprises at least one retention member sized and adapted to be positioned to be effective in retaining the membrane in a substantially fixed position relative to the casing.

Claims 38-40 (canceled)

41. (original) A container for releasing a chemical additive in a liquid fuel composition comprising:

- a casing defining a fuel-impermeable wall structure, a substantially hollow interior and at least one opening in the wall structure;

- a fuel additive composition provided in the interior of said casing, said fuel additive composition comprising a chemical additive soluble in a liquid fuel;

- a fuel-permeable element provided at or substantially directly adjacent the at least one opening of the casing and structured to be effective to provide for release of the chemical additive into the liquid fuel when the liquid fuel is in contact with the casing; and

- an at least partially fuel-soluble seal positioned so that the seal initially extends substantially across the at least one opening.

D-2912

8

42. (original) The container of claim 41 wherein the casing comprises a material selected from the group consisting of metals, polymeric materials, combinations thereof and mixtures thereof.

43. (original) The container of claim 41 wherein the casing is a substantially cylindrical-shaped casing or a substantially bowl-shaped casing.

44. (original) The container of claim 41 wherein the at least partially fuel soluble seal comprises a support structure structured to support the at least partially fuel soluble seal, the support structure being coated with a fuel soluble polymer.

45. (original) The container of claim 44 wherein the support structure comprises a wire screen, a woven cloth or combinations thereof.

46. (original) The container of claim 41 wherein the fuel-permeable element includes a semi-permeable member.

47. (original) The container of claim 41 wherein the fuel-permeable element includes a porous member.

Claims 48-51 (canceled)

52. (previously presented) A container for releasing a chemical additive in a liquid fuel comprising:

a casing defining a fuel-impermeable outer wall structure, a substantially hollow interior and at least two spaced apart openings in the outer wall structure;

a fuel additive composition provided in the interior of said casing, the fuel additive composition comprising a chemical

D-2912

9

additive soluble in a liquid fuel; and

fuel-permeable elements, each of the fuel-permeable elements is provided at or substantially directly adjacent a different one of the at least two openings of the casing, each of the fuel-permeable elements being structured to be effective in controlling release of the chemical additive into the liquid fuel in contact with the casing.

53. (original) The container of claim 52 wherein the casing comprises a material selected from the group consisting of metals, polymeric materials, combinations thereof and mixtures thereof.

54. (original) The container of claim 52 wherein the casing is a substantially cylindrical-shaped casing or a substantially bowl shaped casing.

55. (currently amended) The container of claim 52 wherein each of the fuel permeable elements ~~comprise~~ comprises at least two different types of components, the types of components being selected from the group consisting of (1) a porous member, (2) a semi-permeable member, and (3) an at least partially coolant-soluble seal.

56. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 41 in contact with the fuel composition.

57. (canceled)

58. (original) A method for releasing a chemical additive at a sustained rate into a fuel composition comprising placing the container of claim 52 in contact with the fuel composition.